



0333 034 9433 ALWAYS UN

100kVA - SILENT

Stage V Generator

Power Capacity

90 kw

50 / 60Hz available

50 Hz

Fuel Consumption at 70% 50Hz

17 l/h

Running on internal day tank at 70%

18 hrs

Weight 2,080 kg Noise at 7 metres

55 dB

Dimensions (LxWxH) 2.60 × 1.13 × 1.80 m

CAPABILITY:

 Road towable Central lifting point

· Forklift pockets

connection

• Fully bunded (all liquids)

POWER

Standby (kVA) 110 kVA

Continuous (kVA) 100 kVA

50 / 60Hz available

50 Hz

MOTORS

Engine Model KDI3404TCR Noise at 7 metres

55 dB

Engine Manufacturer Kohler

Alternator Manufacturer

Leroy Sommer

WEIGHT

Weight (kg)

2,380 kg

OPERATIONAL HOURS

Running on internal

day tank at 70%

18 hrs

FLUIDS

FLUID CAPACITIES

Fuel (Litres)

300 Litres

AdBlue (Litre)

36 Litres

FLUID CONSUMPTION

Fuel Consumption at 70% 50Hz

17 l/h

AdBlue per hour at

70% (litre)

2.04 l/h

Dry (kg) 2,080 kg

CONTROL & ELECTRICAL/MECHANICAL **PROTECTION:**

• Bund alarm to avoid any external leaks • 3-way fuel valve for external fuel tank

Compliant Stage V engine technology

o Remote monitoring enabled

noise cancellation

o Super silenced canopy design for additional

o Synchronisation & Load on Demand capable

 Variable speed cooling fans for improved efficiency and noise reduction

Hot dipped galvanised powder coated canopy

- DeepSea 8610 MKII generator controller
- Motorised 4 pole circuit breaker with earth leakage protection
- Hardwire with microswitch protection over busbar door
- Battery isolator
- Emergency Stop
- Engine safety protection shutdown alarm
- DPF filter complete with LED status display


ELECTRICAL CONNECTION

Outgoing Electrical Connections 1 x 125A 3Φ

DIMENSIONS

Dimensions (LxWxH) $2.60 \times 1.13 \times 1.80 \text{ m}$

100KVA - SILENT - STAGE V GENERATOR



COMPREHENSIVE POWER SOLUTIONS ACROSS THE UK





