



0333 034 9433 ALWAYS UN

100kVA

Stage V Generator

Power Capacity

90 kw

50 / 60Hz available

50 Hz

Fuel Consumption at 70% 50Hz

Running on internal

17 I/h

day tank at 70% 25 hrs

Weight 1,680 kg Noise at 7 metres 67 dB

Dimensions (LxWxH) 2.55 × 1.13 × 1.64 m

POWFR

110 kVA

Standby (kVA)

Continuous (kVA)

100 kVA

50 / 60Hz available

50 Hz

MOTORS

Engine Model

Noise at 7 metres

KDI3404TCR

67 dB

Engine Manufacturer Kohler

Alternator Manufacturer

Leroy Sommer

WEIGHT

Dry (kg)

1,680 kg

Weight (kg)

1,980 kg

OPERATIONAL HOURS

Running on internal

day tank at 70%

FLUIDS

FLUID CAPACITIES

FLUID CONSUMPTION

Fuel Consumption at

Fuel (Litres) 275 Litres

70% 50Hz

17 l/h

25 hrs

AdBlue (Litre)

36 Litres

AdBlue per hour at

70% (litre)

1.3 l/h

CAPABILITY:

• Compliant Stage V engine technology

o Synchronisation & Load on Demand capable

Remote monitoring enabled

Hot dipped galvanised powder coated canopy

Road towable

Central lifting point

Forklift pockets

Fully bunded (all liquids)

Bund alarm to avoid any external leaks

3-way fuel valve for external fuel tank

connection

CONTROL & ELECTRICAL/MECHANICAL PROTECTION:

DeepSea 8610 MKII generator controller

• Motorised 4 pole circuit breaker with earth leakage protection

· Hardwire with microswitch protection over busbar door

Battery isolator

Emergency Stop

· Engine safety protection shutdown alarm

DPF filter complete with LED status display

ELECTRICAL CONNECTION

Outgoing Electrical Connections

1 x 125A 3Φ

DIMENSIONS

Dimensions (LxWxH)

2.55 × 1.13 × 1.64 m

100KVA - STAGE V GENERATOR





Summit Power is part of the Summit Rentals Group | Copyright © 2024 Summit Power All rights reserved.