

300kVA

Stage V Generator



Power Capacity 264 kw	50 / 60Hz available 50/60 Hz
Fuel Consumption at 70% 50Hz 50.83 l/h	Running on internal day tank at 70% 18 hrs
Weight 5,100 kg	Noise at 7 metres 68 dB
Dimensions (LxWxH) 4.43 x 1.70 x 2.40 m	

POWER

Standby (kVA) 360 kVA	Continuous (kVA) 330 kVA	50 / 60Hz available 50/60 Hz
---------------------------------	------------------------------------	--

MOTORS

Engine Model DC09	Noise at 7 metres 68 dB
Engine Manufacturer Scania	Alternator Manufacturer Stamford

WEIGHT

Dry (kg) 5,100 kg
Weight (kg) 5,925 kg

CAPABILITY:

- Compliant Stage V engine technology
 - Synchronisation & Load on Demand capable
 - Remote monitoring enabled
- Hot dipped galvanised powder coated canopy
- Central lifting point
- Forklift pockets
- Fully bunded (all liquids)
- Bund alarm to avoid any external leaks
- 3-way fuel valve for external fuel tank connection

CONTROL & ELECTRICAL/MECHANICAL PROTECTION:

- DeepSea 8610 MKII generator controller
- 4 pole circuit breaker with earth leakage protection
- Hardwire with microswitch protection over busbar door
- Battery isolator
- Emergency Stop
- Engine safety protection shutdown alarm
- DPF filter

FLUIDS

FLUID CAPACITIES	FLUID CONSUMPTION	OPERATIONAL HOURS
Fuel (Litres) 910 Litres	Fuel Consumption at 70% 50Hz 50.83 l/h	Running on internal day tank at 70% 18 hrs
AdBlue (Litre) 60 Litres	AdBlue per hour at 70% (litre) 4.12 l/h	

ELECTRICAL CONNECTION


Outgoing Electrical Connections		
4 x 32A 1Φ	1 x 63A 3Φ	1 x 125A 3Φ

DIMENSIONS

Dimensions (LxWxH)
4.43 x 1.70 x 2.40 m

300KVA - STAGE V GENERATOR

DIMENSIONS




COMPREHENSIVE POWER SOLUTIONS ACROSS THE UK



BATTERY ENERGY STORAGE SYSTEMS



FUEL MANAGEMENT



LOAD BANKS

