



0333 034 9433 ALWAYS UN

60kVA

Stage V Generator

Power Capacity

53 kw

50 / 60Hz available

50 Hz

Fuel Consumption at

70% 50Hz 10.8 l/h

Running on internal day tank at 70%

25 hrs

Weight 1,500 kg Noise at 7 metres

65 dB

Dimensions (LxWxH) $2.55 \times 1.13 \times 1.64 \text{ m}$

POWER

Standby (kVA) 64 kVA

Continuous (kVA) 58 kVA

50 / 60Hz available

50 Hz

MOTORS

Engine Model KDI3404TCR Noise at 7 metres

65 dB

Engine Manufacturer Kohler

Alternator Manufacturer **Leroy Sommer**

WEIGHT

Weight (kg)

FLUIDS

FLUID CAPACITIES

Fuel (Litres) 275 Litres

AdBlue (Litre)

Litres

FLUID CONSUMPTION

Fuel Consumption at 70% 50Hz

10.8 l/h

AdBlue per hour at

70% (litre) N/A I/h

Dry (kg) 1,500 kg

1,800 kg

OPERATIONAL HOURS

Running on internal day tank at 70%

25 hrs

CAPABILITY:

- Compliant Stage V engine technology
 - o Synchronisation & Load on Demand capable
 - o Remote monitoring enabled
- Hot dipped galvanised powder coated canopy
- · Road towable
- · Central lifting point
- Forklift pockets
- Fully bunded (all liquids)
- Bund alarm to avoid any external leaks
- 3-way fuel valve for external fuel tank connection

CONTROL & ELECTRICAL/MECHANICAL PROTECTION:

- DeepSea 8610 MKII generator controller
- Motorised 4 pole circuit breaker with earth leakage protection
- Hardwire with microswitch protection over busbar door
- Battery isolator
- Emergency Stop
- Engine safety protection shutdown alarm
- DPF filter complete with LED status display

ELECTRICAL CONNECTION

Outgoing Electrical Connections

1 x 63A 3Φ

1 x 32A 3Φ

1 x 32A 1Φ

DIMENSIONS

Dimensions (LxWxH) $2.55 \times 1.13 \times 1.64 \text{ m}$

60KVA - STAGE V GENERATOR



